DESCRIPTION:

Dura Cover Concrete is a very strong and self-adhesive protection fleece for the temporary protection of walls, floors and stairs. The protection fleece consists of three layers. The bottom layer is liquid tight and provided with an adhesive layer. Dura Cover Concrete can be used horizontal as wel as vertical due to the unique adhesion. The top layer is a strong liquid and oil absorbing non-woven. Dura Cover Concrete provides the best protection possible during intense activities. Dura Cover Concrete protects concrete walls, floors or stairs quickly and easily.



APPLICATIONS:

- → COVERING FOR HARD (PREFAB) CONCRETE FLOORS
- → COVERING FOR HORIZONTAL AND VERTICAL (PREFAB) CONCRETE SURFACES
- → COVERING FOR (PREFAB) CONCRETE WALLS, CORRIDORS AND STAIRS
- * the concrete must be fully cured

CHARACTERISTICS:

- → QUICK AND EASY TO USE
- → SHOCK ABSORBING TOP LAYER
- → LIQUID & OIL ABSORBING TOP LAYER
- → LIQUID DENSE LAYER
- → STRONG ADHESIVE BOTTOM LAYER
- → REUSABLE

TECHNICAL DATA:

Application duration		3 months (max 40° C)
Storage (vertical)		12 months (25°C +/- 10%)
Thickness (0.5kPa)	ISO 9073-2	2.4mm
Weight	ISO 9073-1	350 gr/m2
Tensile strength (MD)	ISO 9073-3	800 N/5cm
Tensile strength (CD)	ISO 9073-3	600 N/5cm
Puncture resistance	ISO 12236	> 2.5 kN
Water absorbtion	ISO 9073-6	450%
Oil absorbtion		470%
Delamination		24 N/10cm
Rolling ball	EN 1721	200mm
Standard Dimensions		25m x 1m

Composition:

Material	Non-woven produced with 100% PP Fiber
Adhesive	Acrylic waterbased
Colour	Gray
Laminated	Laminated with a liquid-tight layer

